



Pozzani Pure Water Plc
 Warwick Road
 Fairfield Industrial Estate
 Louth
 Lincolnshire LN11 0YB
 Telephone: 0845 165 1250
 Telephone: (01507) 608100
 Fax: (01507) 608090
 email:enquiries@pozzani.co.uk
 www.pozzani.co.uk



Water treatment products

N^o10 TWIN - NITRATE REMOVAL AND GENERAL PURPOSE WATER FILTER SYSTEM



No.10 Twin NR600 - IX600 Installation

System Overview

Pozzani have combined a nitrate removal cartridge - NR600, with a general purpose cartridge - IX600 to achieve efficient nitrate reduction together with the reduction of chlorine, dissolved organics, heavy metals and a wide range of other pollutants.

This combination of cartridges makes our twin system one of the most cost effective methods of achieving efficient nitrate reduction and reducing many other unhealthy and unpleasant tasting chemicals and metals.

Cartridges and Performance

NR600 Cartridge contains a special anion exchange resin designed to selectively remove nitrate (NO₃) and nitrite (NO₂). Removal efficiency decreases as the cartridge approaches exhaustion. Nitrate levels over 50mg/l (ppm) will usually need more frequent cartridge changes. (High nitrate users should also consider our RO system with nitrate selective cartridges).

IX600 General purpose multi-stage cartridge will remove chlorine, heavy metals, dissolved organics, oestrogens etc. Dirt and suspended solids are removed down to 5 microns.

Choice of Tap - See pictures at bottom of page

Easy Installation - See picture opposite

Technical Data

Dimensions 350mm (H) 270mm (W) 110mm (D)

Max. Input Pressure 7 bar - 100 psi

Max. Flow Rate 3 litres/min

Cartridge Change **NR600** - On exhaustion or 6 months

IX600 - 6 months

Tap Choice

Whatever your decor, Pozzani offer a choice of tap to suit, chromium (standard), various metal and ceramic painted finishes



Metals taps - chrome, brass, antique brass, brushed and satin stainless, pewter.



Coloured taps - white, black, grey, red, brown, beige and cream.