

AQUARIUS AND QUARTZ WATER COOLERS

Technical Data Sheet



pozzani

DESCRIPTION

This point of use water cooler and dispenser is a convenient and cost effective way of providing a constant supply of filtered fresh water.

Plumbed directly into the mains cold water supply, water is passed through an in-line filtration system, producing crystal clear fresh tasting water.

BENEFITS

- Provides your company with a constant supply of water that smells and tastes better than ordinary tap water.
- Very low running costs – far cheaper than bottle coolers.
- Simple to install and easy to use.
- No bottle storage or heavy lifting required to change over empty bottles.
- No drain required, the cooler has an integrated drip tray.
- Fresh natural tasting water from our quality filtration systems.
- Supplied with our IX600P system. More information overleaf.



IX600P system

SPECIFICATIONS

Performance (litres of water/hour)	20 litres
Cold Tank Capacity	1.5 litres
Weight	17 kg
Voltage	240v AC
Power	600 Watt
Dimensions of Unit	33cm(W) x 34cm(D) x 104cm(H)
Cabinet	Polycarbonate Cabinet
Option of Leak Prevention Device	Yes - at an extra cost
Filter Change Interval	Every 6 months
Connection Kit	3/4" BSPF to 1/4" Push Fit Connector with 2 x In-line Check Valves (to connect to washing machine type connection)



Aquarius Cooler pictured

FEATURES

- **Stylish Design:** Free-standing durable cabinet with plastic panels.
- **Large Removable Drip Tray:** The one-piece drip tray lifts out in seconds for easy sanitisation. It is moulded for durability and is dishwasher safe.
- **Comes with Four Stage Filtration System:** For removing organic chemicals, bad odours, tastes and reducing scale.
- **Connection Kit:** Included – fits on to washing machine connection.
- **Leak Prevention Device:** Optional.

IX600P WATER FILTRATION SYSTEM

- Externally fitted.
- Compact design – housing dimensions 33cm (H) x 16cm (Diameter).
- Flow rate 3 litres per minute.
- Different cartridge options available to remove various contaminants including chlorine, dissolved organics, heavy metals and suspended solids.
- Easy to change cartridge procedure.
- Cartridges lasts up to 6 months each.
- Easy to install. Simple to fit on to the cold water mains copper piping – fittings included. Can also be installed on plastic tubing – additional fittings will be required.
- Maximum input pressure – 7 bar (100 psi)
- Technical help available.



Leak Controller

We recommend the use of a Leak Controller.

Note: Some insurance companies for commercial customers now insist such equipment is protected with a flood protection device such as this.

Non
Return
Valve

