



Pozzani Pure Water Plc
 Warwick Road
 Fairfield Industrial Estate
 Louth
 Lincolnshire LN11 0YB
 Telephone: (01507) 608100
 Fax: (01507) 608090
 email:enquiries@pozzani.co.uk
 www.pozzani.co.uk



Water Treatment Products

CT600 ANTI SCALE SYSTEM



The main benefits of the CT600 system are listed below

- ⦿ Protects combination boilers
- ⦿ Greatly reduces scale in hot water cylinders and boilers
- ⦿ Appliances last longer and work more efficiently
- ⦿ Calcium and rust staining on sinks, taps, showers etc is greatly reduced
- ⦿ Greatly reduced corrosion
- ⦿ Reduces erosion of copper pipework in acidic water
- ⦿ Significantly lowers fuel costs as heating elements are not coated in thick layers of scale
- ⦿ Eliminates the 'nuisance value' of arranging repairs and being without your appliance when it stops

IMPORTANT: Maximum operating pressure rating is 95psi, we recommend the fitting of a pressure regulator if feed pressure is expected to exceed 90psi. Ambient temperature operating range is 5°C to 40°C. Protect system from cold, frost and excess heat.

System Overview

The CT600 is a combined filter system and scale reduction system - it also reduces corrosion and dissolution of pipework in acidic waters.

Maintenance is easy and economic, simply replace the cartridge every six months, registered customers are sent a reminder. There are no messy pastes to mix or cartridges to refill.

TECHNICAL SPECIFICATIONS

Dimensions	Overall height 330mm / width 160mm
Port Sizes	1/2" BSP or 3/4" BSP
Max Pressure	6.5 bar (95 psi)
Temperature	Minimum 5°C ~ Maximum 40°C
Estimated Capacity	250,000 litres
Life Duration	At least 6 months - depending on local conditions
Filtration	5 micron
Weight	2.1Kg

State size of connecting ports e.g. 1/2" BSP (15mm Compression), 3/4" BSP other sizes from 6mm - 22mm available.